



Attention:

Veillez veiller à ce que la lumière ne soit pas fermée par le filetage de la pièce insérée.

Acier, surface sans chrome VI, galvanisé

Référence	G	G1	L	SW	Conditionnement
100-711	M 6 x 1 con	M 6x1	23	12	50
100-721	M 6 x 1 con	M 8x1	23	12	50
100-722	M 8 x 1 con	M 8x1	23	12	50
100-722-1	M 8 x 1,25 con	M 8x1,25	23	12	50
100-723	M 10x1 con	M 8x1	23	12	50
100-724	R 1/8 BSP con	M 8x1	23	12	50
5011-105	M 6 x 1 con	M 10x1	23	13	50
100-732	M 8 x 1 con	M 10x1	23	13	50
100-733	M 10 x 1 con	M 10x1	23	13	50
5011-106	M 10 x 1 con	M 10x1	29	13	50
100-733-10x1,5	M 10 x 1,5 con	M 10x1	23	13	50
100-744	R 1/8 BSP con	Rp 1/8 BSP	23	13	50
100-755	R 1/4 BSP con	RP 1/4 BSP	23	17	50
5011-101	1/8 NPT	1/8 NPT	23	9/16"	50
5011-102	1/8 NPT	1/8 NPT	38	9/16"	50
5011-103	M 6 x 1 con	1/8 NPT	23	9/16"	50
5011-104	1/4-28 UNF	1/8 BSP	23	13	50

Inox 1.4401 / 316 / V4A

5011-201	M 10x1 con	M 10 x 1	23	13	25
5011-202	RP 1/8 BSP con	R 1/8 BSP	23	13	25