



Profile Sealing Ring

PN ([°] /ra)	Dimensions (^{mm} / _{in})						Torque ([°] / _{in.lb})	Weight ([°] / _{in}) ca. per 100
	Thread T	D1	L1	i	S1	S2		
400	M 10 x 1	14	18	8	5	14	12	1,58
5800		.55	.71	.31	.20	.55	8.9	3.47
400	M 12 x 1,5	17	20	12	6	17	25	2,13
5800		.67	.79	.47	.24	.67	18.5	4.69
400	M 14 x 1,5	19	22	12	6	19	45	3,35
5800		.75	.87	.47	.24	.75	33.3	7.38
400	M 16 x 1,5	22	22	12	8	22	55	4,30
5800		.87	.87	.47	.31	.87	40.7	9.46
400	M 18 x 1,5	24	22	12	8	24	70	5,38
5800		.94	.87	.47	.31	.94	51.8	11.83
400	M 20 x 1,5	27	22	14	10	27	80	6,09
5800		1.06	.87	.55	.39	1.06	59.2	13.39
400	M 22 x 1,5	27	22	14	10	27	125	6,77
5800		1.06	.87	.55	.39	1.06	92.5	14.89
400	M 26 x 1,5	32	30	16	12	32	180	14,33
5800		1.26	1.18	.63	.47	1.26	133.2	31.53
400	M 27 x 2	32	28	16	12	32	180	13,23
5800		1.26	1.10	.63	.47	1.26	133.2	29.11
400	M 33 x 2	40	33	18	17	41	250	29,32
5800		1.57	1.30	.71	.67	1.61	185.0	64.50
400	M 42 x 2	50	38	20	22	50	400	57,35
5800		1.97	1.50	.79	.87	1.97	296.0	126.17
400	M 48 x 2	55	40	22	24	55	500	73,79
5800		2.17	1.57	.87	.94	2.17	370.0	162.33