



Series	Tube OD	PN (bar/psi)	Dimensions (mm/in)						Weight (^{kg} /lbs) ca. per 100 ²
	D1		D2	L	L1 ¹	L2	S1	S2	
LL	4	100	3	20	31	12	9	10	0,53
	.16	1450	.12	.79	1.22	.47	.35	.39	1.16
	6	100	4,5	20	32	9	11	12	0,79
	.24	1450	.18	.79	1.26	.35	.43	.47	1.74
	8	100	6	23	35	12	12	14	1,05
	.31	1450	.24	.91	1.38	.47	.47	.55	2.30
	10	100	8	23	35	12	14	17	1,29
	.39	1450	.31	.91	1.38	.47	.55	.67	2.83
	12	100	10	23	35	11	17	19	1,83
.47	1450	.39	.91	1.38	.43	.67	.75	4.03	
L	6	500	4	24	39	10	12	14	1,44
	.24	7250	.16	.94	1.54	.39	.47	.55	3.17
	8	500	6	25	40	11	14	17	1,90
	.31	7250	.24	.98	1.57	.43	.55	.67	4.18
	10	500	8	27	42	13	17	19	2,60
	.39	7250	.31	1.06	1.65	.51	.67	.75	5.72
	12	400	10	28	43	14	19	22	2,67
	.47	5800	.39	1.10	1.69	.55	.75	.87	5.87
	15	400	12	30	46	16	24	27	4,81
	.59	5800	.47	1.18	1.81	.63	.94	1.06	10.57
18	400	15	31	48	16	27	32	6,65	
.71	5800	.59	1.22	1.89	.63	1.06	1.26	14.63	

22	250	19	35	52	20	32	36	8,94
.87	3625	.75	1.38	2.05	.79	1.26	1.42	19.66
28	250	24	36	54	21	41	41	13,90
1.10	3625	.94	1.42	2.13	.83	1.61	1.61	30.57
35	250	30	41	63	20	46	50	21,11
1.38	3625	1.18	1.61	2.48	.79	1.81	1.97	46.43
42	250	36	43	66	21	55	60	29,26
1.65	3625	1.42	1.69	2.60	.83	2.17	2.36	64.38
6	800	4	30	45	16	14	17	2,52
.24	11600	.16	1.18	1.77	.63	.55	.67	5.54
8	800	5	32	47	18	17	19	3,67
.31	11600	.20	1.26	1.85	.71	.67	.75	8.08
10	800	7	32	49	17	19	22	4,23
.39	11600	.28	1.26	1.93	.67	.75	.87	9.30
12	630	8	34	51	19	22	24	5,88
.47	9135	.31	1.34	2.01	.75	.87	.94	12.94
14	630	10	38	57	22	24	27	7,52
.55	9135	.39	1.50	2.24	.87	.94	1.06	16.54
16	630	12	38	57	21	27	30	9,20
.63	9135	.47	1.50	2.24	.83	1.06	1.18	20.25
20	400	16	44	66	23	32	36	14,27
.79	5800	.63	1.73	2.60	.91	1.26	1.42	31.40
25	400	20	50	74	26	41	46	24,99
.98	5800	.79	1.97	2.91	1.02	1.61	1.81	54.97
30	400	25	54	80	27	46	50	33,08
1.18	5800	.98	2.13	3.15	1.06	1.81	1.97	72.77
38	400	32	61	90	29	55	60	53,80
1.50	5800	1.26	2.40	3.54	1.14	2.17	2.36	118.36