



Internal Metallic Sealing Ring

Series	Tube OD (^{mm} / _{in}) D1	PN (^{mm} / _{in})	Dimensions (^{mm} / _{in})										Weight (^{kg} / _{in}) ca. per 100'
			Thread T	D2	D3	L	L1'	L2	L3	L4	S1	S2	
L	6	315	G 1/4	5,5	4	29	37	7,5	14,5	4,5	19	14	3,76
	24	4568		.22	.16	1.14	1.40	.30	.57	.18	.75	.55	8.27
	8	315	G 1/4	5,5	5,5	29	37	7,5	14,5	4,5	19	17	3,74
	31	4568		.22	.22	1.14	1.46	.30	.57	.18	.75	.67	8.23
	10	315	G 1/4	5,5	5,5	30	38	8,5	14,5	4,5	19	19	4,05
	39	4568		.22	.22	1.18	1.50	.33	.57	.18	.75	.75	8.92
	12	315	G 1/4	5,5	5,5	30	38	8,5	14,5	4,5	19	22	4,31
	47	4568		.22	.22	1.18	1.50	.33	.57	.18	.75	.87	9.48
S	6	630	G 1/2	7	4	38	46	11	20	5	27	17	9,16
	24	9135		.28	.16	1.50	1.81	.43	.79	.20	1.06	.67	2.16
	8	630	G 1/2	7	5	38	46	11	20	5	27	19	9,30
	31	9135		.28	.20	1.50	1.81	.43	.79	.20	1.06	.75	2.46
	10	630	G 1/2	7	3,5	38	47	10,5	20	5	27	22	9,39
	39	9135		.28	.14	1.50	1.85	.41	.79	.20	1.06	.67	2.65
	12	630	G 1/2	7	3,5	38	47	10,5	20	5	27	24	9,76
	47	9135		.28	.14	1.50	1.85	.41	.79	.20	1.06	.94	21.47