

Male / Female Whitworth Parallel Pipe Thread (BSPP)

PN (^{mm} / _{inch})	Dimensions (^{mm} / _{inch})							Version	Weight (^{kg} / _{inch}) ca. per 100
	Thread T1	Thread T2	D2	L1	L2	i	S1		
630	G 1/8	G 1/4	4	31	17	8	19	B	4,30
9135			.16	1.22	.67	.31	.75		9,46
630	G 1/8	G 3/8	4	32	17	8	24	B	6,70
9135			.16	1.26	.67	.31	.94		14,74
400	G 1/4	G 1/8	5	29	12	12	19	B	4,40
5800			.20	1.14	.47	.47	.75		9,68
400	G 1/4	G 3/8	5	36	17	12	24	B	7,30
5800			.20	1.42	.67	.47	.94		16,06
400	G 1/4	G 1/2	5	40	20	12	30	B	12,80
5800			.20	1.57	.79	.47	1.18		28,16
400	G 1/4	G 3/4	5	43	22	12	36	B	18,80
5800			.20	1.69	.87	.47	1.42		41,36
400	G 3/8	G 1/8		22,5	8,5	12	22	A	4,20
5800				.89	.33	.47	.87		9,24
400	G 3/8	G 1/4	8	36	17	12	22	B	7,40
5800			.31	1.42	.67	.47	.87		16,28
630	G 3/8	G 1/2	8	41	20	12	30	B	13,60
9135			.31	1.61	.79	.47	1.18		29,92
400	G 3/8	G 3/4	8	44	22	12	36	B	19,70
5800			.31	1.73	.87	.47	1.42		43,34
400	G 1/2	G 1/8		24	8	14	27	A	7,00
5800				.94	.31	.55	1.06		15,40
400	G 1/2	G 1/4		24	12	14	27	A	6,20
5800				.94	.47	.55	1.06		13,64
400	G 1/2	G 3/8	12	37	17	14	27	B	10,40
5800			.47	1.46	.67	.55	1.06		22,88
400	G 1/2	G 3/4	12	46	22	14	36	B	20,10
5800			.47	1.81	.87	.55	1.42		44,22
250	G 1/2	G 1	12	49	24,5	14	41	B	25,10
3625			.47	1.93	.96	.55	1.61		55,22
250	G 1/2	G 1 1/4	10	53	26,5	14	55	B	52,10
3625			.39	2.09	1.04	.55	2.17		114,62